

Document made available under the Patent Cooperation Treaty (PCT)

International application number: PCT/US05/009856

International filing date: 24 March 2005 (24.03.2005)

Document type: Certified copy of priority document

Document details: Country/Office: US
Number: 60/556,350
Filing date: 25 March 2004 (25.03.2004)

Date of receipt at the International Bureau: 25 April 2005 (25.04.2005)

Remark: Priority document submitted or transmitted to the International Bureau in compliance with Rule 17.1(a) or (b)



World Intellectual Property Organization (WIPO) - Geneva, Switzerland
Organisation Mondiale de la Propriété Intellectuelle (OMPI) - Genève, Suisse

1009274



THE UNITED STATES OF AMERICA

TO ALL TO WHOM THESE PRESENTS SHALL COME:

UNITED STATES DEPARTMENT OF COMMERCE

United States Patent and Trademark Office

April 18, 2005

THIS IS TO CERTIFY THAT ANNEXED HERETO IS A TRUE COPY FROM THE RECORDS OF THE UNITED STATES PATENT AND TRADEMARK OFFICE OF THOSE PAPERS OF THE BELOW IDENTIFIED PATENT APPLICATION THAT MET THE REQUIREMENTS TO BE GRANTED A FILING DATE.

APPLICATION NUMBER: 60/556,350

FILING DATE: *March 25, 2004*

RELATED PCT APPLICATION NUMBER: PCT/US05/09856



Certified by

Don W. Dudas

Under Secretary of Commerce
for Intellectual Property
and Director of the United States
Patent and Trademark Office

PROVISIONAL
PATENT APPLICATION
UNDER §111(b)

Attorney Docket No.

091395-9428

First Named Inventor

Xiaolan Ai

Express Mail Label No.

ER 812894736 US

Mail Stop PROVISIONAL PATENT APPLICATION

Commissioner for Patents

P.O. Box 1450

Alexandria, VA 22131-1450

Sir:

Enclosed for filing is a complete provisional patent application entitled "STEERING
WHEEL MOUNTING ASSEMBLY" invented by:

Xiaolan Ai
4480 Noble Loon St. NW
Massillon, OH 44646

David A. Degrange
8238 Grayson Green NW
Massillon, OH 44646

and including the following documents:

Specification including Claim - 9 pages
Abstract of the Disclosure
Drawings - 8 sheets
Return Receipt Postcard

Please charge the \$160.00 filing fee and any other fees associated with this communication to
Deposit Account No. 13-3080. A duplicate copy of this sheet is enclosed.

☒ Customer Number

23585

Respectfully submitted,



Glenn M. Massina
Reg. No. 40,081
Michael Best & Friedrich LLP
3773 Corporate Parkway, Suite 360
Center Valley, Pennsylvania 18034

Date: March 25, 2004

cc: Docketing

Wkg Atty. GMM

Resp Atty. DBS

22151 U.S. PTO
60/556350

STEERING WHEEL MOUNTING ASSEMBLY

BACKGROUND

[0001] The present invention relates to a steering assembly. More particularly, the present invention relates to a steering assembly having a static hub with a steering wheel rotatable thereabout.

[0002] Referring to Fig. 1, a prior art steering assembly 10 is shown. The steering assembly 10 includes a steering wheel 12 mounted on a radial frame 14. The radial frame 14 includes a central hub 16 that is mounted on a steering column 18. Rotation of the steering wheel 12 is translated through the frame 14, and thereby the hub 16, to cause rotation of the steering column 18.

[0003] A mounting frame 20 is attached to and rotates with the radial frame 14. The mounting frame 20 is configured to support an air bag assembly 22 and other components. The air bag assembly 22 is fixed to the mounting frame 20, and therefore, rotates with the steering wheel 12. Since the orientation of the air bag assembly 22 continuously changes with rotation of the steering wheel 12, the air bag assembly 22 must have a substantially symmetrical design so that air bag will deploy with a known configuration no matter the orientation of the air bag assembly 22 at the time of deployment.

[0004] Furthermore, it is not desirable to mount driver controls and displays on the mounting frame 20 since the mounting frame 20 rotates with the steering wheel 12.

SUMMARY

[0005] The present invention relates to a steering wheel mounting assembly. The assembly comprises a stationary support carrier defining first and second ring receiving areas and adapted to be fixed to a vehicle frame. A first drive ring having a first cylindrical raceway is supported in the first ring receiving area and is adapted for connection to a steering wheel. A second drive ring having a second cylindrical raceway is positioned in the second ring receiving area and is adapted for connection to a steering shaft. The second cylindrical raceway is concentric with the first cylindrical raceway. A drive roller assembly is supported within the first and second cylindrical raceways. The drive roller assembly comprises first and second roller planets, each roller planet having raceways configured to engage the first and second cylindrical raceways. A sun roller is supported in frictional engagement with the first and second roller planets. The sun roller is eccentric to the first and second cylindrical raceways. A first loading planet is

frictionally positioned between the sun roller and the first cylindrical raceway and a second loading planet is frictionally positioned between the sun roller and the second cylindrical raceway.

BRIEF DESCRIPTION OF THE DRAWINGS

- [0006] Fig. 1 is a side elevation of a prior art steering assembly in partial cross section;
- [0007] Fig. 2 is an exploded, isometric view of a mounting assembly that is a first embodiment of the present invention;
- [0008] Fig. 3 is an assembled, isometric view of the mounting assembly of Fig. 2 in cross section;
- [0009] Fig. 4 is a front elevation view, in partial section, of the assembled mounting assembly of Fig. 2;
- [0010] Fig. 5 is a cross sectional view along the line 5-5 in Fig. 4;
- [0011] Fig. 6 is a cross sectional view along the line 6-6 in Fig. 4;
- [0012] Fig. 7 is an isometric view, in section, of the stationary support carrier of the present embodiment of the invention;
- [0013] Fig. 8 is an isometric view, in section, of the first drive ring of the present embodiment of the invention;
- [0014] Fig. 9 is an isometric view, in section, of the second drive ring of the present embodiment of the invention;
- [0015] Fig. 10 is an isometric view of the sun roller of the present embodiment of the invention;
- [0016] Fig. 11 is an isometric view of one of the planet rollers of the present embodiment of the invention;
- [0017] Fig. 12 is an isometric view of one of the loading planets of the present embodiment of the invention;
- [0018] Fig. 13 is an isometric view of one of the cover plates of the present embodiment of the invention;
- [0019] Fig. 14 is a schematic view illustrating the relationship of the sun roller, the planet rollers and the loading planets.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0020] The present invention will be described with reference to the accompanying drawing figures wherein like numbers represent like elements throughout. Certain terminology, for example, “top”, “bottom”, “right”, “left”, “front”, “frontward”, “forward”, “back”, “rear” and “rearward”, is used in the following description for relative descriptive clarity only and is not intended to be limiting.

[0021] Referring to Figs. 2-6, a mounting assembly 50 that is a first embodiment of the present invention is shown. The mounting assembly 50 generally comprises a stationary support carrier 60, a first drive ring 100, a second drive ring 120 and a drive roller assembly 140. The stationary support carrier 60 is configured for mounting to the vehicle frame (not shown). The first and second drive rings 100 and 120 are mounted within the stationary support carrier 60. The drive roller assembly 140 provides rotational torque between the first drive ring 100 and the second drive ring 120 such that rotation of a steering wheel (not shown) attached to the first drive ring 100 would cause rotation of a steering shaft (not shown) attached to the second drive ring 120. Cover plates 170, 170' are preferably provided to secure the drive roller assembly 140 within the stationary support carrier 60. The front cover plate 170 is preferably provided with means for supporting desired components, for example, an air bag assembly or driver controls and displays. A wire tube 190 is preferably provided to provide a wire passage from the stationary support carrier 60 through the front cover plate 170.

[0022] The preferred stationary support carrier 60 will be described with reference to Figs. 2, 4 and 7. The stationary support carrier 60 has a radial plate 62. The radial plate 62 is provided with a plurality of threaded holes 64 for fastening the stationary support carrier 60 to the vehicle frame (not shown). The radial plate 62 is provided with a central opening 66 for receiving the drive roller assembly 140. Three supporting columns, a lower column 70 and two side columns 76 and 76, are attached to the radial plate 62 within the central opening 66. Each of the supporting columns 70, 76, 76 has an axial width approximately equal to the width of the drive roller assembly 140 elements. The lower column 70 has a concave radially inner surface 72. An open space 83 for the sun roller 142 is defined above the concave surface 72. As shown in Fig. 4, the sun roller 142 is positioned in the open space 83 such that the sun roller 142 is eccentric to the axis A of the stationary support carrier 60 and the first and second drive rings 100, 120.

[0023] Each side surface 74 of the lower column 70 is also concave. Each lower column side surface 74 is opposed by a concave side surface 77 of a respective side column 76. Each set of opposed side surfaces 74, 77 defines a respective open space 82 configured to receive a

respective one of the planet rollers 150. The two side columns 76 have opposed concave surfaces 79 that define an open area 84 configured to receive the loading planets 160. As shown in Fig. 4, the open space 84 is larger than the diameter of the loading planets 160 such that the loading planets 160 can move within the open area 84 as will be described hereinafter. As shown in Fig. 7, the lower column 70 and side columns 76 each have annular steps 73 and 78, respectively, configured to position and support the cover plates 170, 170' as will be described hereinafter.

[0024] The stationary support carrier 60 has a first annular wall 86 extending from the radial plate 62 to define an area 88 for receiving the first drive ring 100. An annular step 87 at the conjunction of the radial plate 62 and the first annular wall 86 defines the axial position of the first drive ring 100 within area 88. Once the first drive ring 100 is positioned within area 88, it is further secured in the axial direction by a snap ring (not shown) or by roll forming the free end of the annular wall 86.

[0025] The stationary support carrier 60 has a second annular wall 90 extending from the other side of the radial plate 62 to define an area 92 for receiving the second drive ring 120. An annular thrust bearing surface 91 is provided on the radial plate 62 to axially position the second drive ring 120 within the area 92. An annular step 93 at the end of the wall 90 is configured to receive a thrust ring 95, see Fig. 3, to confine the axial position of the second drive ring 120 within the area 92.

[0026] Referring to Fig. 8, the preferred first drive ring 100 is shown. The first drive ring 100 includes an inner race ring 102, a set of rolling elements 114 and an outer race ring 110. The bore of the inner race ring 102 defines the cylindrical raceway 104 of the first drive ring 100. There are through holes 108 on the body of inner race ring 102 for connection with the steering wheel (not shown). The outer surface of the inner race ring 102 is provided with a rolling element raceway 106 and the inner surface of the outer race ring 110 is provided with a rolling element raceway 112. In the illustrated embodiment, the rolling elements 114 are balls and each of the raceways 106, 112 is a circumferential groove configured to receive the balls. Other rolling elements and corresponding raceways may also be utilized. As shown in Figs. 3 and 5-6, the first drive ring 100 is positioned in the area 88 with the outer race ring 110 supported by the first annular wall 86. The rolling elements 114 allow the inner race ring 102, and the interconnected steering wheel (not shown), to rotate freely relative to the outer race ring 110 and thereby the stationary support carrier 60.

[0027] Referring to Figure 9, the preferred second drive ring 120 is illustrated. The second drive ring 120 has an annular body 122. The bore of the annular body 122 defines the cylindrical raceway 123 of the second drive ring 120. The second drive ring 120 is radially supported and positioned by the engagement of the cylindrical raceway 123 with the drive roller assembly 140 as will be described hereinafter. The annular body 122 has two planar surfaces 124 and 126 for axial thrust bearing surfaces. Radially outer surface 127 extending between the planar surfaces 124 and 126 is configured to be spaced from the inner surface of stationary support carrier second annular wall 90 when the second drive ring 120 is positioned within area 92.

[0028] A shaft connector 128 is connected to the annular body 122 through a set of spokes 134. The shaft connector 128 is preferably provided with a through hole 130 and splines or keyways 132 for facilitating connection of a steering shaft or the like to the shaft connector 128. Other connection arrangements may also be provided.

[0029] The preferred drive roller assembly 140 will be described with reference to Figs. 2-4 and 10-13. The drive roller assembly 140 generally comprises a sun roller 142, a pair of planet rollers 150 and a pair of loading planets 160. Referring to Fig. 10, the preferred sun roller 142 has two cylindrical raceways 144 and 146 that are separated by a rib 148. Referring to Fig. 11, the preferred planet rollers 150 each have two cylindrical raceways 152 and 154 separated by a recess 156. At each end surface, there is a journal shaft 158 that lies in the same axis as the raceways 152 and 154. By providing two raceways 144, 146 and 152, 154 on each of the sun and planet rollers 142, 150, the two drive rings 110, 120 are compounded, having at least one common planet or sun roller, to communicate rotational movement and transfer torque from one ring member 100 to the other ring member 120. While it is preferred that the sun roller 142 is formed as a unitary component with a pair of raceways 144, 146 and the planet rollers 150 are formed as unitary components with pairs of raceways 152, 154, it is possible to make one or two of these components as separated components with separate raceways. The sun roller 142 and planet rollers 150 are all preferably manufactured from a rigid material.

[0030] Referring to Fig. 12, each loading planet 160 has a cylindrical body 162 with an opening 164 therethrough. Each loading planet body 162 is flexible relative to the planet rollers 150 and the sun roller 142. The loading planets 160 deform in a diametric direction when assembled between the first and second drive rings 100, 120 and the sun roller 142. This provides a preload that pushes the sun roller 142 downward as will be described hereinafter.

[0031] Referring to Figs. 2-5 and 13, the sun roller 142, planet rollers 150 and the loading rollers 160 are retained axially within the stationary support carrier 60 by attachment of cover

plates 170, 170' to the supporting columns 70, 76, 76. Each cover plate 170, 170' is preferably provided with two bearing sleeves 176 configured to receive the journal shaft 158 extending from the planet rollers 150. As shown in Fig. 13, the front cover plate 170 is preferably provided with mounting features, for example, connection holes 180, 182, for mounting an air bag assembly, instrument panels or displays. The front cover plate 170 is also provided with a primary through hole 174 and a secondary through hole 178. The secondary through hole 178 is configured to receive and support a portion of the wire tube 190 as will be described hereinafter. The rear cover plate 170' can be formed in the same configuration as the front cover plate 170 to minimize manufacturing, however, the rear cover plate 170' can be formed without mounting features and the secondary through hole 178.

[0032] Referring to Figs. 4-6, the drive roller assembly 140 is positioned in the stationary support carrier 60 with the sun planet 142 in opening 83, the roller planets 150 in respective openings 82, and the loading planets 160 are positioned in the opening 84. The roller planets 150 are supported by the first and second drive rings 100 and 120 with the first raceways 152 bearing on the first drive ring cylindrical raceway 104 and the second raceways 154 bearing on the second drive ring cylindrical raceway 123. Each journal shaft 158 is received in and supported by a respective bearing sleeve 176.

[0033] The sun roller 142 is supported between and in frictional contact with the two roller planets 150. The sun roller rib 158 is received in each planet roller recess 156 to maintain the sun roller 142 axially aligned with the planet rollers 150. The planet roller raceways 152 bear against the sun roller raceway 144 and the planet roller raceways 154 bear against the sun roller raceway 146. The sun roller 142 is supported below the axis A of the stationary support carrier 60 and first and second drive rings 100, 120 such that the sun roller 142 is eccentric to the first and second drive rings 100, 120.

[0034] One of the loading planets 160 is positioned between sun roller raceway 144 and the first drive ring cylindrical raceway 104 and a second of the loading planets 160 is positioned between the sun roller raceway 146 and the second drive ring cylindrical raceway 123. The loading planets 160 preferably have a diameter greater than the respective distances between the sun raceways 144 and 146 and the ring drive raceways 104 and 123 such that the loading planets 160 provide a preload on the sun roller 106. The sun roller rib 148 axially positions the loading planets 160 as shown in Fig. 4.

[0035] A wire passage is provided by wire tube 190 as shown in Figs. 2-3 and 5-6. The wire tube 190 has a radial portion 192 that provides a radial passage 194 and an axial portion 196 that

provides an axial passage 198 interconnected with the radial passage 194. The axial portion 196 is provided with a mounting recess 199 configured to snap on to the secondary through hole 178 of the cover plate 170. The axial portion 196 extends through the opening 164 of one of the loading rollers 160 and the radial portion 192 extends between an axial gap between the two loading rollers 160 and through the opening 68 cut on the stationary supporting carrier 60.

[0036] Having described the components of the preferred mounting assembly 50, its operation will now be described with reference to Figs. 4 and 14. The roller planets 150 back up the sun roller 142. The downward force F_0 (loading force) from the loading planets 160 on the sun roller 142 is balanced by the backing forces F_b from planets 150 as shown in Figure 14. The angle between the two backing forces, denoted as α , can be designed close to 180 degrees. Thus a small loading force F_0 can result in large backing forces F_b which in turn cause large normal contact force between the roller planets 150 and the drive rings 100, 120. These large normal contact forces provide adequate friction force between the roller planets 150 and the drive ring 100, 120 to ensure torque transfer between the two drive rings 100, 120.

[0037] As the operator steers the vehicle, the first drive ring inner race ring 102 turns with the steering wheel (not shown) in the same direction. Contact between the first drive ring inner ring raceway 104 and the roller planet raceways 152 and the loading planet 160 causes the roller planet raceways 152 and the loading planet 160 to rotate in the same direction as the first drive ring inner ring 102. Motion of the first drive ring inner ring 102 pulls the loading planet 160 into a convergent gap formed between the first drive ring inner ring 102 and the sun roller 142. This further increases the loading force F_0 for the first drive ring 100. The roller planets 150 consequently drive the sun roller 142 in the opposite direction. As the sun roller 142 rotates, it also pulls the other loading planet 160 into a convergent gap formed between the second drive body 122 and the sun roller 142. This, in a similar way, further increases the loading force F_0 for the second drive ring 120. As the roller planets 150 rotate they drive the second drive ring 120 in the same direction as the planet rollers 150 and the first drive ring inner ring 102. Therefore, the drive roller assembly 140 provides a 1:1 speed ratio between the two ring drives 100 and 120. Any overturning moment on the first drive ring inner ring 102 from the steering wheel is taken directly by the bearings 114 to the stationary supporting carrier 60. Co-owned U.S. Patent Application No. 10/298,762, incorporated herein by reference, further describes the drive roller assembly 140.

[0038] The present invention provides zero backlash at frictional contacts. There will be no lash between the first drive ring 100 connected to a steering wheel and the second drive ring 120

connected to the steering shaft. Furthermore, the drive roller assembly 140 is smooth and quiet operation. The friction drive eliminates the lash and variation in torque experienced during operation of gear driven steering systems.

*

*

*

What is claimed is:

1. A steering wheel mounting assembly comprising:
 - a stationary support carrier defining first and second ring receiving areas and adapted to be fixed to a vehicle frame;
 - a first drive ring having a first cylindrical raceway and supported in the first ring receiving area and adapted for connection to a steering wheel;
 - a second drive ring having a second cylindrical raceway and positioned in the second ring receiving area and adapted for connection to a steering shaft, the second cylindrical raceway being concentric with the first cylindrical raceway; and
 - a drive roller assembly supported within the first and second cylindrical raceways, the drive roller assembly comprising:
 - first and second roller planets, each roller planet having raceways configured to engage the first and second cylindrical raceways;
 - a sun roller supported in frictional engagement with the first and second roller planets, the sun roller being eccentric to the first and second cylindrical raceways;
 - a first loading planet frictionally positioned between the sun roller and the first cylindrical raceway; and
 - a second loading planet frictionally positioned between the sun roller and the second cylindrical raceway.

ABSTRACT

[0039] A steering wheel mounting assembly comprising a stationary support carrier defining first and second ring receiving areas. A first drive ring having a first cylindrical raceway is supported in the first ring receiving area. A second drive ring having a second cylindrical raceway is positioned in the second ring receiving area. A drive roller assembly is supported within the first and second cylindrical raceways. The drive roller assembly comprises first and second roller planets, a sun roller supported in frictional engagement with the first and second roller planets, a first loading planet frictionally positioned between the sun roller and the first cylindrical raceway and a second loading planet frictionally positioned between the sun roller and the second cylindrical raceway.

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

FIG. 1
 (Prior Art)






Fig. 2









Fig. 7




Fig. 8

